# SAFETY DATA SHEET

1. Identification

Product number 1000000660

Product identifier 10 OZ DURAGLOSS 265 ULTIMATE DTL LB 6PK

**Company information** BROTHERS RESEARCH Corp.

2245 AIR PARK DRIVE

BURLINGTON, NC 27216 United States

Emergency telephone US

Emergency telephone outside

US

1-866-836-8855 1-952-852-4646

Version # 01

Recommended use COATING
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSerious eye damage/eye irritationCategory 2AReproductive toxicityCategory 1A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard

Category 1

Category 2

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard Not classified.

OSHA defined hazards

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye

irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and

keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting.

If eye irritation persists: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20 - 40
Butane		106-97-8	10 - 20
Odorless Mineral Spirits		64741-65-7	10 - 20
Propane		74-98-6	10 - 20
Solvent Naphtha (petroleum), Light Aliph.		64742-89-8	10 - 20
n-Heptane		142-82-5	2.5 - 10
Cyclohexane		110-82-7	1 - 2.5
Dead Record		N/A	0.1 - 1
Toluene		108-88-3	0.1 - 1
Other components below reportable levels	3		10 - 20

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance.

Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a

POISON CENTER or doctor/physician if you feel unwell.

**Skin contact**Immediately take off all contaminated clothing. Immediately flush skin with plenty of water. Get medical attention if irritation develops or persists. For minor skin contact, avoid spreading material

medical attention if irritation develops or persists. For minor skin contact, avoid spreading material

on unaffected skin. Wash clothing separately before reuse.

**Eye contact**Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists. If

eye irritation persists: Get medical advice/attention.

**Ingestion**If material is ingested, immediately contact a poison control center. Have victim rinse mouth thoroughly with water. Call a physician or poison control center immediately. If vomiting occurs

naturally, have victim lean forward to reduce risk of aspiration. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way

valve or other proper respiratory medical device.

**Most important** Irritation of eyes and mucous membranes. May cause drowsiness or dizziness. symptoms/effects, acute and

delayed
Indication of immediate

Indication of immediate medical attention and special treatment needed

**General information** 

Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: get medical attention/advice. IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.

# 5. Fire-fighting measures

Suitable extinguishing media Powder. Alcohol resistant foam. Carbon dioxide (CO2).

**Unsuitable extinguishing** Do not use a solid water stream as it may scatter and spread fire. **media** 

**Specific hazards arising from the chemical**Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.

**Special protective equipment and precautions for firefighters**Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stay upwind. Avoid inhalation of vapors or mists. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle or store near an open flame, heat or other sources of ignition. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks, and flame. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep in a well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. Keep the container dry. Keep this material away from food, drink and animal feed. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

# 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
,		300 ppm	
Dead Record (CAS N/A)	PEL	1800 mg/m3	
		500 ppm	
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m3	

US. OSHA Table Z-1 Limit Components		Гуре	(=0 01 10 10 10 100	Val	ue
				500	) ppm
Propane (CAS 74-98-6)	F	PEL			00 mg/m3
1 (	•	•			00 ppm
US. OSHA Table Z-2 (29 C	ER 1910 1000)				,
Components		Гуре		Val	ue
Toluene (CAS 108-88-3)	(	Ceiling	9	300	) ppm
	7	ΓWA		200	) ppm
ACGIH					
Components	7	Гуре		Val	ue
Solvent Naphtha (petroleum), Light Aliph.	٦	ΓWA		400	) ppm
(CAS 64742-89-8)					
<b>US. ACGIH Threshold Lin</b>	nit Values				
Components	7	Гуре		Val	ue
Acetone (CAS 67-64-1)	5	STEL		750	) ppm
·	٦	ΓWΑ		500	) ppm
Butane (CAS 106-97-8)	9	STEL			00 ppm
Cyclohexane (CAS 110-82-7)	٦	ΓWΑ			) ppm
Dead Record (CAS N/A)	ד	ΓWA		50	ppm
n-Heptane (CAS 142-82-5)	5	STEL			) ppm
		ΓWΑ			) ppm
Toluene (CAS 108-88-3)	7	ΓWA			ppm
US. NIOSH: Pocket Guide	to Chemical Haza	rds			
Components		Гуре		Val	ue
Acetone (CAS 67-64-1)	7	ΓWΑ			) mg/m3
					) ppm
Butane (CAS 106-97-8)	7	ΓWΑ			00 mg/m3
					) ppm
Cyclohexane (CAS 110-82-7)	7	ΓWA		105	50 mg/m3
				300	) ppm
Dead Record (CAS N/A)	7	ΓWΑ			) mg/m3
				50	ppm
n-Heptane (CAS 142-82-5)	(	Ceiling	9		00 mg/m3
					) ppm
	ד	ΓWΑ			) mg/m3
				85	ppm
Propane (CAS 74-98-6)	٦	ΓWΑ			00 mg/m3
Toluene (CAS 108-88-3)	5	STEL			00 ppm 0 mg/m3
	•				) ppm
	Т	ΓWA			5 mg/m3
		•			) ppm
ogical limit values					
ACGIH Biological Exposu	re Indices				
Components	Value		Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l		Acetone	Urine	*
Dead Record (CAS N/A)	0.4 mg/l		2,5-Hexanedio	Urine	*
_ = = = = = = = = = = = = = = = = = = =	g/!		n, without	56	
			hydrolysis		
T   (0.4.0, 4.0.0, 0.0.0)	0.2 ma/a		o-Cresol, with	Creatinine in	<b>+</b>
Toluene (CAS 108-88-3)	0.3 mg/g		hydrolysis	Creatimine in	

### **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

<sup>\* -</sup> For sampling details, please see the source document.

**Exposure guidelines** No Exposure standards allocated.

US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering

controls

Ensure adequate ventilation, especially in confined areas. Provide eyewash station.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear eye/face protection. Wear safety glasses with side shields (or goggles). Do not get this

material in contact with eyes.

Hand protection Wear protective gloves.

Skin protection

Other Do not get this material in contact with skin. Wear chemical protective equipment that is

specifically recommended by the manufacturer. It may provide little or no thermal protection.

**Respiratory protection** Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are

exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not

provide adequate protection.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get this material in contact with skin. Avoid contact with eyes. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

Appearance Compressed liquefied gas.

Physical state Gas.
Form Aerosol.
Color Clear.
Odor fruity

Odor threshold Not available.

pH Not applicable estimated

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point -156.0 °F (-104.4 °C) (Propellant) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 37 - 47 psig @ 70F estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Auto-ignition temperature Not available.

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Heat of combustion 34.69 kJ/g estimated Heat of combustion (NFPA 34.69 kJ/g estimated

30B)

Specific gravity 0.682 estimated estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Risk of ignition.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

**Conditions to avoid** Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Incompatible materials Strong oxidizing agents. Acids. Fluorine. Chlorine. Nitrates.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

## Information on likely routes of exposure

**Ingestion** May be fatal if swallowed and enters airways.

**Inhalation** May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. Narcotic

effects.

**Skin contact** Not available.

**Eye contact** Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## Information on toxicological effects

Acute toxicity Acute LD50: 5412 mg/kg, Rat, Dermal

Acute LC50: 293 mg/l/4h, Rat, Inhalation

May be fatal if swallowed and enters airways. Narcotic effects.

Product Species Test Results

10 OZ DURAGLOSS 265 ULTIMATE DTL LB 6PK (CAS Mixture)

Acute

Dermal

LD50 Rat 5412 mg/kg

Inhalation

LC50 Rat 293 mg/l/4h
Components Species Test Results

Acetone (CAS 67-64-1)

Acute

Dermal

LD50 Guinea pig > 7426 mg/kg, 24 Hours

> 9.4 ml/kg, 24 Hours

Rabbit > 7426 mg/kg, 24 Hours

> 9.4 ml/kg, 24 Hours

Inhalation

LC50 Rat 55700 ppm, 3 Hours

132 mg/l, 3 Hours

50.1 mg/l

Oral LD50

Rat 5800 mg/kg

Components	Species	Test Results
		2.2 ml/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Cyclohexane (CAS 110-82-7		ŭ
Acute	,	
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		v v
LC50	Rat	> 32880 mg/m3, 4 Hours
		> 5540 ppm, 4 Hours
Dead Record (CAS N/A)		о о рр,
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours
• •		> 5 ml/kg, 4 Hours
Inhalation		> 5 mi/kg, 4 mours
LC50	Mouse	48000 mg/l, 4 Hours
2000		-
	Rat	> 5000 ppm, 24 Hours
		> 31.86 mg/l
		73860 ppm, 4 Hours
Oral		
LD50	Rat	38500 mg/kg
		24 ml/kg
n-Heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 29.29 mg/l, 4 Hours
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Solvent Naphtha (petroleum)	, Light Aliph. (CAS 64742-89-8)	-
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5020 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/ll, 4 Hours
		~ 4.30 mg/i, 4 mours

Components	Species	Test Results
Oral	_	
LD50	Rat	4820 mg/kg
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation		
LC50	Mouse	6405 - 7436 ppm, 6 Hours
		5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours
		12.5 - 28.8 mg/l, 4 Hours
Oral		
LD50	Rat	5000 mg/kg

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Not applicable.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity Not applicable.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity** May damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

Narcotic effects.

Specific target organ toxicity -

repeated exposure

Respiratory system. Skin. Central nervous system. Eyes. Peripheral nervous system.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. Not

expected to be hazardous by WHMIS criteria.

# 12. Ecological information

**Ecotoxicity** LC50: 8703 mg/L, Fish, 96.00 Hours

EC50: 28104 mg/L, Daphnia, 48.00 Hours IC50: 17903 mg/L, Algae, 72.00 Hours

Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product		Species	Test Results
10 OZ DURAGLOSS	265 ULTIMATE DT	L LB 6PK (CAS Mixture)	
Aquatic			
Algae	IC50	Algae	17903 mg/L, 72 Hours
Crustacea	EC50	Daphnia	28104 mg/L, 48 Hours
Fish	LC50	Fish	8703 mg/L, 96 Hours
Components		Species	Test Results
Acetone (CAS 67-64-	1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours

Components		Species	Test Results
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Cyclohexane (CAS 110-82-	7)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours
Dead Record (CAS N/A)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours
n-Heptane (CAS 142-82-5)			
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Odorless Mineral Spirits (CA	AS 64741-65-7)		
Aquatic			
Algae	IC50	Algae	30000 mg/L, 72 Hours
Solvent Naphtha (petroleum	n), Light Aliph. (C	AS 64742-89-8)	
Aquatic			
Algae	IC50	Algae	4700 mg/L, 72 Hours
Γoluene (CAS 108-88-3)			
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Butane	2.89
Cyclohexane	3.44
n-Heptane	4.66
Propane	2.36
Toluene	2.73

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not

contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code D018: Waste Benzene

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

**US RCRA Hazardous Waste U List: Reference** 

Acetone (CAS 67-64-1) U002 Cyclohexane (CAS 110-82-7) U056 Toluene (CAS 108-88-3) U220 Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

# 14. Transport information

DOT

UN1950 **UN number** 

**UN** proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

N82 Special provisions 306 Packaging exceptions Packaging non bulk None None Packaging bulk

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA** 

UN1950 **UN** number

**UN** proper shipping name Aerosols, flammable

Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed. **Packaging Exceptions** LTD QTY

**IMDG** 

**UN number** UN1950 **UN** proper shipping name **AEROSOLS** 

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Not applicable. Packing group

**Environmental hazards** 

Yes Marine pollutant F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

LTD QTY

the IBC Code



IATA; IMDG



# Marine pollutant



**General information** 

IMDG Regulated Marine Pollutant.

# 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

# **CERCLA Hazardous Substance List (40 CFR 302.4)**

Acetone (CAS 67-64-1) Listed. Cyclohexane (CAS 110-82-7) Listed. Toluene (CAS 108-88-3) Listed.

# SARA 304 Emergency release notification

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No **Hazard categories** 

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

# SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

## SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Cyclohexane	110-82-7	1 - 2.5	
Toluene	108-88-3	0.1 - 1	
Ethyl Benzene	100-41-4	0.01 - 0.1	

#### Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

# Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532 Toluene (CAS 108-88-3) 6594

# Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV Toluene (CAS 108-88-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

Acetone (CAS 67-64-1) 6532 Toluene (CAS 108-88-3) 594

#### **US state regulations**

WARNING: This product contains chemicals known to the State of California to cause cancer.

#### **US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1) Butane (CAS 106-97-8)

Cyclohexane (CAS 110-82-7) n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

# US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Cyclohexane (CAS 110-82-7)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Cyclohexane (CAS 110-82-7)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

# **US. Rhode Island RTK**

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Cyclohexane (CAS 110-82-7)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

## **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

# US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

## US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

# US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

## **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

# 16. Other information, including date of preparation or last revision

Issue date 03-02-2015

Version # 01

**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently

available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with

any other materials or in any process, unless specified in the text.

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).