505, DURAGLOSS WATER SPOT REMOVER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/28/2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : 505, DURAGLOSS WATER SPOT REMOVER

Product code : Part# 505 22oz, 506 Gal

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Brothers Research Corporation
2245 Airpark Drive
Burlington, NC 27216
T 336-229-6480

1.4. Emergency telephone number

Emergency number : 800-424-9300
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :

GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : P264 - Wash ... thoroughly after handling
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical advice/attention

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
1-propanol	(CAS No) 71-23-8	1 - 2	Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336
butyl glycolether	(CAS No) 111-76-2	0.5 - 1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove the victim into fresh air. If not breathing give artificial respiration. Get immediate medical advice/attention. Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Move victim away from exposure and into fresh air. Rinse immediately with plenty of water for 15 minutes. If eye irritation persists: Get medical advice/attention. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Do not induce vomiting. Call a physician or poison control center immediately. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide. Dry chemical powder. Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Water can be used to keep exposed containers cool, to protect;. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Complete protective clothing. Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spill on vermiculite floor absorbent or other absorbent material.

6.1.1. For non-emergency personnel

Protective equipment : Protective goggles. Protective clothing.

Emergency procedures : Stop spill at source, prevent from spreading. No open flames, no sparks, and no smoking. Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required. Safety glasses. Protective gloves. Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Containers of this material may be hazardous when empited. All hazard precautions give should be observed.

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Containers may be hazardous when emptied. Since emptied containers retain product residues, all hazard precautions given in the data sheet should be observed. All 5 gallon and larger metal containers hsould be grounded or bonded when material is transferred. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep away from heat, sparks, and flames. Emptied containers may retain product residues. Precautions apply to emptied containers. Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

505, DURAGLOSS WATER SPOT REMOVER		
ACGIH	Not applicable	
OSHA	Not applicable	
DNEL	DNEL	≈

1-propanol (71-23-8)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m³)	500 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm

butyl glycolether (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
OSHA	Not applicable	

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Appearance	:	Light Blue Liquid.
Color	:	Blue
Odor	:	Sweet
Odor threshold	:	No data available
pH	:	3 - 4
Relative evaporation rate (butyl acetate=1)	:	No data available
Melting point	:	No Data
Freezing point	:	No data available
Boiling point	:	180 °F @ 760 mmHg
Flash point	:	> 160 °F
Auto-ignition temperature	:	NA
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	No data available
Vapor pressure	:	33 .0 mmHg @ 68.0 F
Relative vapor density at 20 °C	:	No data available
Relative density	:	1 @ 60.0 F
Solubility	:	Water: > 0.01
Log Pow	:	No data available
Log Kow	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Explosive limits	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Acids. Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

None Expected. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

1-propanol (71-23-8)	
LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rabbit	4049 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	9.8 mg/l/4h (Rat)

1-propanol (71-23-8)	
ATE US (dermal)	4049.000 mg/kg body weight
ATE US (vapors)	9.800 mg/l/4h
ATE US (dust, mist)	9.800 mg/l/4h

butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	2.2 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	450 ppm/4h (Rat; Experimental value)
ATE US (oral)	1746.000 mg/kg body weight
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (gases)	450.000 ppmV/4h
ATE US (vapors)	2.200 mg/l/4h
ATE US (dust, mist)	2.200 mg/l/4h

Skin corrosion/irritation : Not classified
pH: 3 - 4

Serious eye damage/irritation : Causes serious eye irritation.
pH: 3 - 4

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

butyl glycolether (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

1-propanol (71-23-8)	
LC50 fish 1	3200 mg/l 48 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	4415 mg/l (24 h; Daphnia magna)
EC50 other aquatic organisms 1	4168 mg/l (48 h; Protozoa)
LC50 fish 2	4480 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 2	3644 mg/l (48 h; Daphnia magna)
TLM fish 1	200 - 500,Gobio gobio
TLM other aquatic organisms 1	100 - 1000,96 h
Threshold limit algae 1	2000 mg/l (Selenastrum capricornutum)
Threshold limit algae 2	3100 mg/l (168 h; Scenedesmus quadricauda)

butyl glycolether (111-76-2)	
LC50 fish 1	1474 ppm (96 h; Oncorhynchus mykiss)
EC50 Daphnia 1	1550 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	911 mg/l (72 h; Pseudokirchneriella subcapitata)
Threshold limit algae 2	88 mg/l (72 h; Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

505, DURAGLOSS WATER SPOT REMOVER	
Persistence and degradability	Not established.

1-propanol (71-23-8)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions.
Biochemical oxygen demand (BOD)	0.47 - 1.63 g O_2/g substance
Chemical oxygen demand (COD)	2.23 g O_2/g substance
ThOD	2.4 g O_2/g substance
BOD (% of ThOD)	0.20 - 0.44 % ThOD

butyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil. Photooxidation in the air.

12.3. Bioaccumulative potential

505, DURAGLOSS WATER SPOT REMOVER	
Bioaccumulative potential	Not established.

1-propanol (71-23-8)	
Log Pow	0.25 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

butyl glycolether (111-76-2)	
Log Pow	0.81 (Test data; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

1-propanol (71-23-8)	
Surface tension	0.024 N/m (20 °C)

butyl glycolether (111-76-2)	
Surface tension	0.065 N/m (20 °C; 003)

12.5. Other adverse effects

Effect on ozone layer :

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

505, DURAGLOSS WATER SPOT REMOVER

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

1-propanol (71-23-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

butyl glycolether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

15.3. US State regulations

1-propanol (71-23-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

butyl glycolether (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 05/28/2015

Other information : None.

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product