

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/28/2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : 581, DURAGLOSS MARINE/RV BLACK STREAK ELIMINATOR

Product code : PART# 581 22oz, 582 Gal

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Brothers Research Corporation 2245 Airpark Drive Burlington, NC 27216 T 336-229-6480

1.4. Emergency telephone number

Emergency number : 800-424-9300 Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 4 H227 Skin Irrit. 2 H315 Eye Dam. 1 H318

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS05

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid

H315 - Causes skin irritation

H318 - Causes serious eye damage

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P264 - Wash ... thoroughly after handling

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of water/...

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P310 - Immediately call a POISON CENTER, a doctor P321 - Specific treatment (see ... on this label)

P321 - Specific treatment (see ... on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention

P362 - Take off contaminated clothing and wash before reuse P370+P378 - In case of fire: Use ... to extinguish

P370+P378 - In case of fire: Use ... to extinguish P403+P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

09/28/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
butyl glycolether	(CAS No) 111-76-2	2-5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
disodium metasilicate	(CAS No) 6834-92-0	1 - 3	Skin Corr. 1A, H314 STOT SE 3, H335

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation

occurs: Get medical advice/attention. Specific treatment (see ... on this label).

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

09/28/2015 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor.

Hygiene measures : Wash ... thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container

closed when not in use.

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

581, DURAGLOSS MARINE/RV BLACK STREAK ELIMINATOR	
ACGIH	Not applicable
OSHA	Not applicable

butyl glycolether (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
OSHA	Not applicable	

disodium metasilicate (6834-92-0)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses. Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Blue Liquid.Color: BlueOdor: Coconut

Odor threshold : No data available

pH : 11 - 12

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : No Data

Freezing point : No data available

Boiling point : $212 \,^{\circ}F$ Flash point : $> \,^{\circ}F$

09/28/2015 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : 141 @ 130.0 F
Relative vapor density at 20 °C : No data available

Relative density : H20=1 Specific gravity / density : <

Solubility : Soluble in water.

Water: Solubility in water of component(s) of the mixture :

•: •: > 18 g/100ml

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	2.2 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	450 ppm/4h (Rat; Experimental value)
ATE US (oral)	1746.000 mg/kg body weight
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (gases)	450.000 ppmV/4h
ATE US (vapors)	2.200 mg/l/4h
ATE US (dust, mist)	2.200 mg/l/4h

disodium metasilicate (6834-92-0)		
	LD50 dermal rat	> 5000 mg/kg body weight (Rat: Read-across: OECD 402: Acute Dermal Toxicity)

Skin corrosion/irritation : Causes skin irritation.

pH: 11 - 12

09/28/2015 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation : Causes serious eye damage.

pH: 11 - 12

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

butyl glycolether (111-76-2)

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

butyl glycolether (111-76-2)	
LC50 fish 1	1474 ppm (96 h; Oncorhynchus mykiss)
EC50 Daphnia 1	1550 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	911 mg/l (72 h; Pseudokirchneriella subcapitata)
Threshold limit algae 2	88 mg/l (72 h; Pseudokirchneriella subcapitata)

disodium metasilicate (6834-92-0)	
LC50 fish 1	210 mg/l (96 h; Brachydanio rerio)
EC50 Daphnia 1	216 mg/l (96 h; Daphnia magna; GLP)
LC50 fish 2	2320 mg/l (96 h; Gambusia affinis)
EC50 Daphnia 2	632 mg/l (96 h; Lymnaea sp.)
Threshold limit algae 1	207 mg/l (72 h; Scenedesmus subspicatus; GLP)

12.2. Persistence and degradability

581, DURAGLOSS MARINE/RV BLACK STREA	AK ELIMINATOR
Persistence and degradability	Not established.

butyl glycolether (111-76-2)

Persistence and degradability

Readily biodegradable in water. Low potential for adsorption in soil. Photooxidation in the air.

disodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Bioaccumulative potential Not established.

butyl glycolether (111-76-2)	
Log Pow	0.81 (Test data; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

09/28/2015 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

disodium metasilicate (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Mobility in soil

butyl glycolether (111-76-2)	
Surface tension	0.065 N/m (20 °C; 003)

12.5. Other adverse effects

Effect on ozone layer :

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN3253 Disodium trioxosilicate, 8, III

UN-No.(DOT) : UN3253

Proper Shipping Name (DOT) : Disodium trioxosilicate

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102)

IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).

IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner.

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Packaging Non Bulk (49 CFR 173.xxx) : 213

DOT Packaging Bulk (49 CFR 173.xxx) : 240

DOT Quantity Limitations Passenger aircraft/rail : 25 kg (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 100 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

09/28/2015 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

581, DURAGLOSS MARINE/RV BLACK STREAK ELIMINATOR

Listed on the United States TSCA (Toxic Substances Control Act) inventory

butyl glycolether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

disodium metasilicate (6834-92-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

1

15.3. US State regulations

butyl glycolether (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 05/28/2015 Other information : None.

09/28/2015 EN (English US) 7/8

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

kt of 11-prilages.	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

09/28/2015 EN (English US) 8/8